





Fasson® Products

MORE THAN 35 YEARS OF TRUSTED PERFORMANCE

Avery Dennison provides high quality Fasson brand pressure-sensitive HVAC/R tapes that deliver a fast, permanent bond providing an airtight moisture barrier for sealing duct board, flexible duct and insulation facings.

Contractors can chose from a complete line of foil, FSK, film and cloth duct tapes. Fasson® 0800 and Fasson® 0810 tapes carry a 20-year limited product warranty.

FOR BEST RESULTS

Fasson brand tapes adhere best on clean dry surfaces. For a strong bond, maintain tension when applying tape and then squeegee tape flat. Be sure to store tape in a cool, dry place and to rotate stock.





HVAC FASTENING SYSTEMS

Product	Description	Available Sizes	Rolls / Case	Order Number
Fasson® 0810	2 mil, high tensile strength aluminum foil, meets UL® standard 181A-P & B-FX for high performance closure systems on rigid fiberglass duct board and flexible duct, uses a 2.6 mil, white, high shear, acrylic adhesive that carries a 20-year limited warranty .	2.5" x 60 yds. 3.0" x 60 yds.	16 16	87412 02160180 87412 03000180
Fasson® 0800	2 mil, high tensile strength aluminum foil, meets UL® standard 181A-P & B-FX for high performance closure systems on rigid fiberglass duct board and flexible duct; uses a 2.4 mil, high shear, acrylic adhesive that carries a 20-year limited warranty ; economically priced.	2.5" x 60 yds. 3.0" x 60 yds.	16 16	56477 02160180 56477 03000180
Fasson® 0802	2 mil, dead-soft aluminum foil, coated one side with a 2.1 mil, quick-stick, synthetic rubber adhesive, offers a strong bond to a variety of surfaces. UL® 723 classified.	2.0" x 50 yds. 2.5" x 50 yds. 3.0" x 50 yds.	24 16 16	50058 02000150 50058 02160150 50058 03000150
Fasson® 0821	A tri-directional Foil Scrim Kraft (FSK) facestock that matches FSK faced insulation. Coated on one side with an aggressive, 2 mil, synthetic rubber-based adhesive. UL® 723 classified.	3.0" x 50 yds.	16	50334 03000150
Fasson® 0817	2 mil, dead-soft aluminum foil, coated one side with a 2 mil, quick stick, cold-temperature synthetic rubber-based adhesive. Features a strong bond to a variety of surfaces. UL® 723 classified.	2.0" x 50 yds. 3.0" x 50 yds.	24 16	56384 02000150 56384 03000150
Fasson® 0827	A tri-directional Foil Scrim Kraft (FSK) facestock that matches FSK faced insulation. Coated on one side with an aggressive, 2 mil, quick-stick, cold-temperature synthetic rubber-based adhesive. UL® 723 classified.	3.0" x 50 yds.	16	56535 03000150
Fasson® 1803	1.5 mil, dead-soft aluminum foil, coated one side with a 1.8 mil, quick-stick, synthetic rubber adhesive system, offers a strong bond to a variety of surfaces. UL® 723 classified.	2.0" x 50 yds. 3.0" x 50 yds.	24 16	55869 02000150 55869 03000150

CLOTH DUCT TAPES

Product	Description	Available Sizes*	Color	Order Number
Fasson® 950	10 mil, economy grade, cloth duct tape with a maximum performance temperature of 200°F. UL® 723 classified.	48mm x 55m	Black Silver	58984 01280180 58983 01280180
Fasson® 955	12 mil, metalized cloth duct tape with a maximum performance temperature of 200°F. UL® 723 classified.	48mm x 55m 72mm x 55m	Metalized Metalized	58988 01280180 58988 02270180
Fasson® 957	14 mil, UL® 181B-FX classified, Premium HVAC Grade cloth duct tape with a maximum performance temperature of 200°F. Heavy duty polyethylene and premium cloth ensure an airtight moisture barrier.	48mm x 55m 48mm x 55m 72mm x 55m	Black Metalized Metalized	58306 01280180 58307 01280180 58307 02270180

FILM TAPES

Product	Description	Available Sizes*	Color	Order Number
Fasson® FAS-FLEX	Printed metallized BOPP used for connecting, joining and sealing flexible air ducts. UL® 181B-FX classified.	48mm x 110m 48mm x 110m	Metalized Black	58343 01280360 58342 01280360
Fasson® Line Set Tape	UV-resistant, 1.4 mil acrylic adhesive film tape designed for taping elastomeric insulation on HVAC line sets.	48mm x 55m	Black	57656 01280180

ACCESSORIES

Product	Description	Available Sizes	Cans / Case	Order Number
Fasson® 1000S	High viscosity, excellent tack, multi-purpose spray adhesive for most lightweight materials. Specially formulated for fast and secure bonds, excellent properties for bonding dissimilar substrates and VOC compliant. Designed to meet current government requirements.	17 fluid ounces	12	589390

^{*48}mm = 24 rolls per case 72mm = 16 rolls per case

Proud Members Of:









Please refer to **Tapes.AveryDennison.com** for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2019 Avery Dennison Corporation. All rights reserved. Fasson® and Avery Dennison® are registered trademarks of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.

ADV# AD 0012, 8/19, 250. POD



Performance

Asia Pacific Kunshan, China, NO. 618 Nanhe Road Kunshan Economic & Technological Zone China 215335

Phone: +86 512 57155001 Fax: +86 512 57155059

Europe Tieblokkenlaan 1 B-2300 Turnhout Belgium Phone: +32 (0)14 40 48 11

Fax: +32 (0)14 40 48 55

North America 250 Chester Street Painesville, Ohio 44077 USA

Phone: +1 866-462-8379 Fax: +1 888-358-4469